

Explore the BUFR WORLD

Introduction to BUFR decoding with ecCodes

Marijana Crepulja

Analyst, Observation team

marijana.crepulja@ecmwf.int





Python decoding BUFR

Input arguments

Output arguments

Open BUFR file

```
ifile = open(filename)
```

ifile: id of the opened file to be used in all the file functions

filename: name of the file to be open

Close BUFR file

```
ifile.close()
```

ifile: the id of the file to be closed



Python decoding BUFR

Input arguments
Output arguments

- Load in memory a message from a file.

```
ibufr = codes_bufr_new_from_file(ifile)
```

ifile: object of the file opened with `codes_open_file`

ibufr: id of the message loaded in memory

- Free the memory for the message referred as `ibufr`

```
codes_release(ibufr)
```



- Check!

```
if ibufr is None:
```

```
...
```



Python decoding BUFR

- Get the value of a scalars from a message

```
value = codes_get(ibufr, key)
```

ibufr: id of the message loaded in memory

key: key of the variable

value: value of variable

Input arguments

Output arguments

- Get the array values of a variable from a message

```
value = codes_get_array(ibufr, key)
```

ibufr: id of the message loaded in memory

key : key of the variable

value: an array of variable values



Python decoding BUFR

- We need to instruct ecCodes to unpack the data values

```
codes_set(ibufr, 'unpack', 1)
```

Input arguments
Output arguments

- Loop over messages

```
while 1:
```

```
    ibufr = codes_bufr_new_from_file(ifile)
```

```
    codes_set(ibufr, 'unpack', 1)
```

```
    ! Read variables values
```

```
    year = codes_get(ibufr, 'year')
```

```
    latitude = codes_get_array(ibufr, 'latitude')
```

```
    ! Release the BUFR message
```

```
    codes_release(ibufr)
```